

Ohebné komínové vložky

Materiál: korozi vzdorná ocel dle SN EN 10088 -1
cena za 1m v roztaženém stavu

vnit ní pr m r (mm)	podtlakový provoz KO 1.4301 tl.0,3 mm suchý plyn	podtlakový provoz KO 1.4404 tl.0,3 mm mokrý plyn, lehký olej	podtlakový provoz KO 1.4404 tl.0,4 mm tuhá paliva, d evo
60	/	/	/
80	/	/	/
100	393,-	/	/
110	393,-	503,-	/
120	414,-	532,-	/
125	435,-	557,-	/
130	446,-	572,-	687,-
140	490,-	627,-	731,-
150	524,-	672,-	782,-
160	562,-	720,-	835,-
170	/	/	889,-
180	627,-	803,-	944,-
200	696,-	893,-	1.091,-

vnit ní pr m r (mm)	p etlakový provoz KO 1.4404 tl.2x0,12 mm plyn, kou ovody
60	251,-
80	335,-
100	419,-
110	461,-
120	503,-
125	525,-
130	545,-
140	586,-
150	629,-
160	670,-
170	/
180	755,-
200	838,-

vnit ní pr m r (mm)	vzduchotechnika AL 99,5 tl.0,5 mm rozvod vzduchu
60	/
80	/
100	125,-
110	134,-
120	141,-
125	/
130	150,-
140	173,-
150	193,-
160	215,-
170	/
180	238,-
200	269,-

vnit ní pr m r (mm)	navád cí hlavice
80 (závit)	120,-
90	105,-
100	110,-
110	115,-
120	120,-
130	125,-
140	130,-
150	135,-
160	140,-
180	155,-
200	165,-